

# ring0 Slim-Vertical-Direct

## DATA SHEET

PROJECT: \_\_\_\_\_

TYPE: \_\_\_\_\_

NOTES: \_\_\_\_\_

QUANTITY: \_\_\_\_\_

DATE: \_\_\_\_\_

### GENERAL

**Product Code:**

RSPV-D-450 / RSPV-D-600 / RSPV-D-800 /  
RSPV-D-1000 / RSP-D-1200

**Luminaire Type:**

Pendant in Vertical

**Body Construction:**

Highest grade extruded aluminum

**Body Surface Finishes:**

Texture White / Texture Black / Any other RAL  
color available on request

**IP Rating:**

40

### PHYSICAL

**Dimension  $\Phi$  x H x W:**

450x25x20mm 600x25x20mm 800x25x20mm  
1000x25x20mm 1200x25x20mm

**Fixing System:**

1500mm long steel wires with height  
adjustment system

### LED

**Light Source:**

LED

**CCT:**

3000K / 4000K / 5700K / TW (Tunable White)  
-2700-6500K

**CRI:**

80+, 90+ (Available on request)

**MacAdam Step:**

3

### OPTICAL

**Light Distribution:**

Direct

**Diffuser:**

Satin finished Opal Diffuser

### ELECTRICAL

**System Wattage:**

25W / 35W / 40W / 60W / 70W

**Luminous Flux:**

1750lm / 2450lm / 2800lm / 4200lm / 4900lm

**Power Factor:**

0.94

### DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue Dimmable

Bluetooth 4.0 CASAMBI remote control through App

