

# ring0 Slim Bunch Direct-Indirect

## DATA SHEET

PROJECT: \_\_\_\_\_

TYPE: \_\_\_\_\_

NOTES: \_\_\_\_\_

QUANTITY: \_\_\_\_\_

DATE: \_\_\_\_\_

### GENERAL

**Product Code:**

RSPB-DI-12108 / RSPB-DI-1086 / RSPB-DI-864

**Luminaire Type:**

Pendant

**Body Construction:**

Highest grade extruded aluminum

**Body Surface Finishes:**

Texture White / Texture Black / Any other RAL color available on request

**IP Rating:**

40



### PHYSICAL

**Dimension  $\Phi$  x H x W:**

1200-1000-800x40x20mm

1000-800-600x40x20mm

800-600-450x40x20mm

**Fixing System:**

1500mm long steel wires with height adjustment system

### LED

**Light Source:**

LED

**CCT:**

3000K / 4000K / 5700K / TW (Tuneable White)  
]2700-6500K

**CRI:**

80+, 90+ (Available on request)

**MacAdam Step:**

3

### OPTICAL

**Light Distribution:**

Direct-Indirect

**Diffuser:**

Satin finished Opal Diffuser

### ELECTRICAL

**System Wattage:**

220W / 180W / 150W

**Luminous Flux:**

15400lm / 12600lm / 10500lm

**Power Factor:**

0.94

### DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue Dimmable

Bluetooth 4.0 CASAMBI remote control through App