

Soft Square - Ceiling Mounted

DATA SHEET

PROJECT: _____

TYPE: _____

NOTES: _____

QUANTITY: _____

DATE: _____

GENERAL

Product Code:

SSC-300 / SSC-400 / SSC-600 / SSC-900 /
SSC-1200

Luminaire Type:

Ceiling Mounted

Body Construction:

Highest grade extruded aluminum

Body Surface Finishes:

Texture White / Texture Black / Texture Grey /
Any RAL color possible on request.

IP Rating:

40



PHYSICAL

Dimension L x W x H:

300x300x85mm 400x400x85mm 600x600x85mm
900x900x85mm 1200x1200x85mm

Fixing System:

Ceiling Mounted with Screw

LED

Light Source:

LED

CCT:

3000K / 4000K / 5700K / TW (Tunable White)
-2700-6500K Possible only for 600mm / 900mm
/ 1200mm

CRI:

80+, 90+ (Available on request)

MacAdam Step:

3

OPTICAL

Light Distribution:

Direct

Diffuser:

Satin Finished PC Opal Diffuser, Micro-
Prismatic Diffuser

UGR:

< 22 with Opal Diffuser, < 19 with Micro-
Prismatic Diffuser

ELECTRICAL

System Wattage:

25W / 35W / 45W / 75W / 100W

Luminous Flux:

1750lm / 2450lm / 3150lm / 5250lm / 7000lm

Power Factor:

0.94

DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue Dimmable

Bluetooth 4.0 CASAMBI remote control through App