

Linear 25

DATA SHEET

PROJECT: _____

TYPE: _____

NOTES: _____

QUANTITY: _____

DATE: _____

GENERAL

Product Code:

PM-25 / CM-25 / RM-25

Luminaire Type:

Pendant / Ceiling Mount / Recessed

Body Construction:

Highest grade extruded aluminum

Body Surface Finishes:

Natural anodized finish / Texture White / Texture Black / Any RAL color possible on request.

IP Rating:

40




PHYSICAL

Dimension W x H x L*:

25 x 14 x 1130mm

Fixing System:

Suspend with 1500mm long steel wires with height adjustment system / ceiling mount with screw / Recessed mount with mounting brackets



LED

Light Source:

LED

CCT:

3000K / 4000K / 5700K / TW (Tunable White)
2700-6500K

CRI:

80+, 90+, (Available on request)

MacAdam Step:

3

OPTICAL

Light Distribution:

Direct

Diffuser:

Satin Finished PC Opal Diffuser

UGR:

< 22

ELECTRICAL

System Wattage:

5W / 10W / 15W / 20W

Luminous Flux:

445lm at Luminaire level / 890lm at Luminaire level / 1335lm at Luminaire level / 1780lm at Luminaire level

Power Factor:

0.94

DRIVER

Non-Dimmable Remote

DALI Dimmable Remote

0-10V Analogue Dimmable Remote

Bluetooth 4.0 CASAMBI remote control through App

*The length mentioned here is only for a single unit but can be changed as per your preference.

*customized product, please contact us for required form and patterns.