

# Linear 25

## DATA SHEET

PROJECT: \_\_\_\_\_

TYPE: \_\_\_\_\_

NOTES: \_\_\_\_\_

QUANTITY: \_\_\_\_\_

DATE: \_\_\_\_\_

### GENERAL

**Product Code:**

PM-25 / CM-25 / RM-25

**Luminaire Type:**

Pendant / Ceiling Mount / Recessed

**Body Construction:**

Highest grade extruded aluminum

**Body Surface Finishes:**

Natural anodized finish / Texture White / Texture Black / Any RAL color possible on request.

**IP Rating:**

40




### PHYSICAL

**Dimension W x H x L\*:**

25 x 14 x 1130mm

**Fixing System:**

Suspend with 1500mm long steel wires with height adjustment system / ceiling mount with screw / Recessed mount with mounting brackets



### LED

**Light Source:**

LED

**CCT:**

3000K / 4000K / 5700K / TW (Tunable White)  
2700-6500K

**CRI:**

80+, 90+, (Available on request)

**MacAdam Step:**

3

### OPTICAL

**Light Distribution:**

Direct

**Diffuser:**

Satin Finished PC Opal Diffuser

**UGR:**

< 22

### ELECTRICAL

**System Wattage:**

5W / 10W / 15W / 20W

**Luminous Flux:**

445lm at Luminaire level / 890lm at Luminaire level / 1335lm at Luminaire level / 1780lm at Luminaire level

**Power Factor:**

0.94

### DRIVER

Non-Dimmable Remote

DALI Dimmable Remote

0-10V Analogue Dimmable Remote

Bluetooth 4.0 CASAMBI remote control through App

\*The length mentioned here is only for a single unit but can be changed as per your preference.

\*customized product, please contact us for required form and patterns.