

# Flow - Ceiling- Direct

## DATA SHEET

PROJECT: \_\_\_\_\_

TYPE: \_\_\_\_\_

NOTES: \_\_\_\_\_

QUANTITY: \_\_\_\_\_

DATE: \_\_\_\_\_

### GENERAL

**Product Code:**

FCM

**Luminaire Type:**

Ceiling Mounted

**Body Construction:**


Highest grade extruded aluminum Aluminum profile single max. length available in 3380mm

**Body Surface Finishes:**

Natural anodized finish / Texture White / Texture Black / Texture Grey / Any Other RAL color possible on Request

**IP Rating:**

40



### PHYSICAL

**Dimension W x H x L\*:**

172x43x1140mm

**Fixing System:**

Ceiling Mounted with Screw

### LED

**Light Source:**

LED

**CCT:**

3000K / 4000K / 5700K / TW (Tunable White)  
2700-6500K

**CRI:**

80+, 90+, (Available on request)

**MacAdam Step:**

3

### OPTICAL

**Light Distribution:**

Direct

**Diffuser:**

Micro-Prismatic diffuser from Germany with one 20mm mm color mixing sheet Diffuser single max. length available in 3380mm

**UGR:**

< 19

### ELECTRICAL

**System Wattage:**

30W / 40W

**Luminous Flux:**

2400 lm at Luminaire level / 3200 lm at Luminaire level

**Power Factor:**

0.94

### DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue Dimmable

Bluetooth 4.0 CASAMBI remote control through App

\*The length mentioned here is only for a single unit but can be changed as per your preference.

\*customized product, please contact us for required form and patterns.