

Round - Recessed

DATA SHEET

GENERAL

Product Code:
RSR-300 / RSR-400 / RSR-600 / RSR-900 / RSR-1200

Luminaire Type:
Recessed

Body Construction:
Highest grade extruded aluminum

Body Surface Finishes:
Texture White / Texture Black / Texture Grey / Any Other RAL color possible on Request

IP Rating:
40

PHYSICAL

Dimension Ø x H:
300x85mm 400x85mm 600x85mm 900x85mm 1200x85mm

Fixing System:
Mounting Bracket for Recessed

LED

Light Source:
LED

CCT:
3000K / 4000K / 5700K / TW (Tunable White)
2700-6500K Possible only for 600 mm / 900 mm / 1200mm

CRI:
80+, 90+ (Available on request)

MacAdam Step:
3

OPTICAL

Light Distribution:
Direct

Diffuser:
Satin Finished PC Opal Diffuser, Micro-Prismatic Diffuser

UGR:
< 22 with Opal Diffuser, < 19 with Micro-Prismatic Diffuser

ELECTRICAL

System Wattage:
25W / 35W / 45W / 75W / 100W

Luminous Flux:
1750 lm / 2450 lm / 3150 lm / 5250 lm / 7000 lm

Power Factor:
0.94

DRIVER

Non-Dimmable
DALI Dimmable
0-10V Analogue
Bluetooth 4.0 CASAMBI remote control through App

PROJECT:

TYPE:

NOTES:

QUANTITY:

DATE:

