

# Soft Square - Recessed

## DATA SHEET

### GENERAL

**Product Code:**  
SSR-300 / SSR-400 / SSR-600 / SSR-900 /  
SSP-1200

**Luminaire Type:**  
Recessed

**Body Construction:**  
Highest grade extruded aluminum

**Body Surface Finishes:**  
Texture White / Texture Black / Texture Grey /  
Any RAL color possible on request.

**IP Rating:**  
40

### PHYSICAL

**Dimension L x W x H:**  
300x300x85mm 400x400x85mm 600x600x85mm  
900x900x85mm 1200x1200x85mm

**Fixing System:**  
Mounting Bracket for Recessed

### LED

**Light Source:**  
LED

**CCT:**  
3000K / 4000K / 5700K / TW (Tunable White )  
-2700-6500K Possible only for 600mm / 900mm  
/ 1200mm

**CRI:**  
80+, 90+ (Available on request)

**MacAdam Step:**  
3

### OPTICAL

**Light Distribution:**  
Direct

**Diffuser:**  
Satin Finished PC Opal Diffuser, Micro-  
Prismatic Diffuser

**UGR:**  
< 22 with Opal Diffuser, < 19 with Micro-  
Prismatic Diffuser

### ELECTRICAL

**System Wattage:**  
25W / 35W / 45W / 75W / 100W

**Luminous Flux:**  
1750lm / 2450lm / 3150lm / 5250lm / 7000lm

**Power Factor:**  
0.94

### DRIVER

Non-Dimmable  
DALI Dimmable  
0-10V Analogue Dimmable  
Bluetooth 4.0 CASAMBI remote control through App

PROJECT: \_\_\_\_\_

TYPE: \_\_\_\_\_

NOTES: \_\_\_\_\_

QUANTITY: \_\_\_\_\_

DATE: \_\_\_\_\_

