# An Architectural Lighting Company

## Linear 25 DATA SHEET

GENERAL

Product Code: PM-25 / CM-25 / RM-25

Luminaire Type: Pendant / Ceiling Mount / Recessed

**Body Construction:** Highest grade extruded aluminum

#### **Body Surface Finishes:**

Natural anodized finish / Texture White / Texture Black / Any RAL color possible on request.

IP Rating: 40

PHYSICAL

#### Dimension W x H x L\*:

25 x 14 x 1130mm

### Fixing System:

Suspend with 1500mm long steel wires with height adjustment system / ceiling mount with screw / Recessed mount with mounting brackets

#### LED

#### Light Source:

LED

#### CCT:

3000K / 4000K / 5700K / TW (Tunable White) 2700-6500K

#### CRI:

80+, 90+, (Available on request)

#### MacAdam Step:

3

#### OPTICAL

Light Distribution: Direct

#### **Diffuser:**

Satin Finished PC Opal Diffuser

UGR:

#### < 22

ELECTRICAL

#### System Wattage:

5W / 10W / 15W / 20W

#### Luminous Flux:

445lm at Luminaire level / 890lm at Luminaire level / 1335lm at Luminaire level / 1780lm at Luminaire leve

# **Power Factor:** 0.94

#### DRIVER

Non-Dimmable Remote DALI Dimmable Remote 0-10V Analogue Dimmable Remote Bluetooth 4.0 CASAMBI remote control through App

\*The length mentioned here is only for a single unit but can be changed as per your preference. \*customized product, please contact us for required form and patterns.

PROJECT:		
TYPE:		
NOTES:		
QUANTITY:		
DATE:		
DATE:		

www.vizionlighting.com



