

# Linear 80 Recessed with Trim

#### GENERAL

Product Code: RMWT-80-D

Luminaire Type: Recessed

#### Body Construction:

Highest grade extruded aluminum Aluminum profile single max. length available in 3380mm

### Body Surface Finishes:

Natural anodized finish / Texture White / Texture Black / Texture Grey / Any Other RAL color possible on Request (Any Contrast color also possible)

IP Rating: 40

. .

PHYSICAL

## **Dimension W x H x L\*:** 80x80x1130mm

### Fixing System:

Recessed Mounting Brackets

### LED

Light Source:

### LED

CCT: 3000K / 4000K / 5700K / TW (Tunable White) 2700-6500K CRI:

80+, 90+, (Available on request)

### MacAdam Step:

3

### OPTICAL

### Light Distribution:

Direct

**Diffuser:** Satin Finished PC Opal Diffuser, Micro-

Prismatic Diffuser

### UGR:

< 22 with Opal Diffuser, < 19 with Micro-Prismatic Diffuser

### ELECTRICAL

System Wattage: 23W / 27W

Luminous Flux: 2047 lm at Luminaire level / 2295 lm at Luminaire level Power Factor: 0.94

### DRIVER

Non-Dimmable DALI Dimmable 0-10V Analogue Dimmable Bluetooth 4.0 CASAMBI remote control through App

\*The length mentioned here is only for a single unit but can be changed as per your preference. \*customized product, please contact us for required form and patterns.

Ρ	PROJECT:	
Т	TYPE:	
N	NOTES:	
Q	QUANTITY:	
D	DATE:	



