



①

Groove

Highly functional luminaire, classic and stylish. Its minimal, slim form can be unified into any interior design.



A minimalist, dark-colored rectangular light fixture is shown against a dark background. The fixture has a glowing horizontal strip of light along its length, creating a strong contrast. The lighting is soft and focused on the fixture, highlighting its simple, functional design.

Reverence for simplicity and utility

What is Groove


Glare-free luminaries that generate a fluid gradation of light.

The entire product family impresses with its typically recessed and curved aluminium profile.

Offers high visual comfort enhanced by the slender, minimalistic profile.


UGR<16





Perfect lighting for every space.

Light throw that **won't disturb glare from projectors**. Highly recommended for board rooms.



Endless design possibilities.

Recessed light source lends to a **cozy and soft light distribution**, in any atmosphere.

Optimal lighting system.

Defined light throw avoids light pilferage.



Barely there, yet impactful.

Invisible light source that provides **high visual comfort**, preventing any eye contact with it.



Recessed luminaire. Perfect for expansive spaces.



Fusion of form
with function,
bathed in luxury








Illumination for inspiration

Groove 70

▸ Groove 70+




PENDANT

Luminaire suspended from the ceiling with a transparent wire.

DIRECT

Downward light distribution provides uniform lighting.



Product Code
GPM+70-D

Luminaire Type
Pendant

Dimension W x H x L*
70x110x1130 mm

Fixing System
1500mm long steel wires with height adjustment system

Couplers
90° Ceiling to ceiling, 90° Ceiling to Wall, 120° Y shape

Light Distribution
Direct

HE (High Efficiency)
23W (System Wattage)


HO (High Output)
27W (System Wattage)

HE Luminous Flux
2047 lm at Luminaire level

HO Luminous Flux
2295 lm at Luminaire level

DIRECT-INDIRECT

Provides light upward and downward. Can bring a softer ambient glow.



Product Code
GPM+70-DI

Luminaire Type
Pendant

Dimension W x H x L*
70x110x1130 mm

Fixing System
1500mm long steel wires with height adjustment system

Couplers
90° Ceiling to ceiling, 90° Ceiling to Wall, 120° Y shape

Light Distribution
Direct-Indirect

HE (High Efficiency)
23W /11w (System Wattage)

HO (High Output)
27W /13w (System Wattage)

HE Luminous Flux
3026 lm at Luminaire level


HO Luminous Flux
3400 lm. at Luminaire level

RECESSED

Luminaire directly installed into a hollow opening in a ceiling.

DIRECT

Downward light distribution provides uniform lighting.



Product Code
GRM+70-D

Luminaire Type
Recessed Trimless

Dimension W x H x L*
70x110x1130 mm

Fixing System
Recessed Mounting Brackets

Couplers
90° Ceiling to ceiling, 90° Ceiling to Wall, 120° Y shape

Light Distribution
Direct

HE (High Efficiency)
23W (System Wattage)

HO (High Output)
27W (System Wattage)

HE Luminous Flux
2047 lm at Luminaire level


HO Luminous Flux
2295 lm at Luminaire level

CEILING

Flush-mount luminaries attached to the ceiling.

DIRECT

Downward light distribution provides uniform lighting.



Product Code
GCM+70-D

Luminaire Type
Ceiling Mounted

Dimension W x H x L*
70x110x1130 mm

Fixing System
Surface Mount with Screw

Couplers
90° Ceiling to ceiling, 90° Ceiling to Wall, 120° Y shape

Light Distribution
Direct

HE (High Efficiency)
23W (System Wattage)

HO (High Output)
27W (System Wattage)

HE Luminous Flux
2047 lm at Luminaire level

HO Luminous Flux
2295 lm at Luminaire level

All Groove 70+ carry the following specifications

GENERAL	Body Construction	Highest grade extruded aluminum Aluminum profile single max. length available in 3380mm
	Surface Finishes	Natural anodized finish Texture White Texture Black Texture Grey Any Other RAL color possible on Request
	End Cap	Screw less End cap made of Aluminum
	LED Batten	Made of aluminum extrusion in white powder coated, is fixed in with Snap-in technique
	IP Rating	40

LED	Light Source	LED
	CCT	3000K 4000K 5700K TW (Tunable White) 2700-6500K
	CRI	80+, 90+ [Available on request]
	UGR MacAdam Step	<16 3

Power Factor 0.94
Push-in Wago terminals for quick and easy wiring between two led modules
Quick coupling BJB Connector to simplify connections between the subsequent modules.

Diffuser Satin finished PC Opat Diffuser or **Micro-Prismatic diffuser**, is fixed with Snap-in technique, Diffuser single max. length available in 3380mm

Driver Non-Dimmable
DALI Dimmable
0-10V Analogue Dimmable
Bluetooth 4.0
CASAMBI remote control through App

All Groove 70+ are available in the following colours



*The length mentioned here is only for a single unit but can be changed as per your preference.