

9

## Round

Adds a delicate touch of lightness with its classic, subtle design, fusing with any interior design.

---








## Round

Round can be mounted in three ways

### RECESSED

Luminaire directly installed into a hollow opening in a ceiling.



**Product Code**  
RSR-300 | RSR-400 | RSR-600  
RSR-900 | RSR-1200

**Luminaire Type**  
Recessed

**Dimension  $\Phi$  x H**  
300x85 mm | 400x85 mm  
600x85 mm | 900x85 mm  
1200x85 mm


**Fixing System**  
Mounting Bracket for Recessed

**System Wattage**  
25W | 35W | 45W | 75W | 100W

**Luminous Flux**  
1750 lm | 2450 lm | 3150 lm  
5250 lm | 7000 lm

### CEILING

Flush-mount luminaires attached to the ceiling.



**Product Code**  
RSC-300 | RSC-400 | RSC-600  
RSC-900 | RSC-1200

**Luminaire Type**  
Ceiling Mounted

**Dimension  $\Phi$  x H**  
300x85 mm | 400x85 mm  
600x85 mm | 900x85 mm  
1200x85 mm


**Fixing System**  
Surface Mounted with Screw

**System Wattage**  
25W | 35W | 45W | 75W | 100W

**Luminous Flux**  
1750 lm | 2450 lm | 3150 lm  
5250 lm | 7000 lm

### PENDANT

Luminaire suspended from the ceiling with a transparent wire.



#### Pendant 300 | 400

**Product Code**  
RSP-300 | RSP-400

**Luminaire Type**  
Pendant

**Dimension  $\Phi$  x H**  
300x85 mm | 400x85 mm

**Fixing System**  
1500 mm long steel wires with height adjustment system

**System Wattage**  
25W | 35W

**Luminous Flux**  
1750 lm | 2450 lm

#### Pendant 600-1200

**Product Code**  
RSP-600 | RSP-900 | RSP-1200

**Luminaire Type**  
Pendant


**Dimension  $\Phi$  x H**  
600x85 mm | 900x85 mm  
1200x85 mm

**Fixing System**  
1500 mm long steel wires with height adjustment system

**System Wattage**  
45W | 75W | 100W

**Luminous Flux**  
3150 lm | 5250 lm | 7000 lm

The Round Pendant 600-1200 luminaire has two wiring options



All Round are available in the following colours

GENERAL	<b>Body Construction</b>	Highest grade extruded aluminum
	<b>Surface Finishes</b>	Texture White Texture Black Texture Grey Any Other RAL color possible on Request
	<b>IP Rating</b>	40

LED	<b>Light Source</b>	LED
	<b>CCT</b>	3000K   4000K   5700K   TW (Tunable White) 2700-6500K Possible only for 600 mm   900 mm
	<b>CRI</b>	80+, 90+ (Available on request)
	<b>MacAdam Step</b>	3

<b>Power Factor</b>	0.94
---------------------	------

OPTICAL	<b>Light Distribution</b>	Direct
	<b>Diffuser</b>	Satin finished Opal Diffuser

<b>Driver</b>	Non-Dimmable DALI Dimmable 0-10V Analogue Bluetooth 4.0 CASAMBI remote control through App
---------------	--

All Round are available in the following colours

