

5

Soft triang0

Impeccably
moulded. Sets fresh
benchmarks in design,
flexibly achieving
diverse interior looks.





Originality is nothing but
an extrapolation of truth




Soft triang0

Soft triang0 can be mounted in three ways

RECESSED

Luminaire directly installed into a hollow opening in a ceiling.



Product Code
STR-450 | STR-600 | STR-900

Luminaire Type
Recessed

Dimension L x H
450 | 600 | 900x85 mm

Fixing System
Mounting Bracket for Recessed

System Wattage
35W | 45W | 75W

Luminous Flux
2450 lm | 3150 lm | 5250 lm

CEILING

Flush-mount luminaires attached to the ceiling.



Product Code
STC-450 | STC-600 | STC-900

Luminaire Type
Ceiling Mounted

Dimension L x H
450 | 600 | 900x85 mm


Fixing System
Ceiling Mounted with Screw

System Wattage
35W | 45W | 75W

Luminous Flux
2450 lm | 3150 lm | 5250 lm

PENDANT

Luminaire suspended from the ceiling with a transparent wire.



Pendant 450

Product Code
STP-450

Luminaire Type
Pendant

Dimension L x H
450x85 mm

Fixing System
1500 mm long steel wires with height adjustment system

System Wattage
35W

Luminous Flux
2450 lm

Pendant 600 | 900

Product Code
STP-600 | STP-900

Luminaire Type
Pendant


Dimension L x H
600 | 900x85 mm

Fixing System
1500 mm long steel wires with height adjustment system

System Wattage
45W | 75W

Luminous Flux
3150 lm | 5250 lm

The Soft triang0 Pendant 600 | 900 luminaire has two wiring options



All Soft triang0 carry the following specifications

| | | |
|---------|--------------------------|---|
| GENERAL | Body Construction | Highest grade extruded aluminum |
| | Surface Finishes | Texture White Texture Black Texture Grey Any Other RAL color possible on Request |
| | IP Rating | 40 |

| | | |
|-----|-------------------------|---|
| LED | Light Source CCT | LED 3000K 4000K 5700K TW (Tunable White) 2700-6500K Possible only for 600 mm 900 mm |
| | CRI | 80+, 90+ (Available on request) |
| | MacAdam Step | 3 |

Power Factor 0.94

| | | |
|---------|---------------------------|------------------------------|
| OPTICAL | Light Distribution | Direct |
| | Diffuser | Satin finished Opal Diffuser |

| | |
|---------------|--|
| Driver | Non-Dimmable DALI Dimmable 0-10V Analogue Bluetooth 4.0 CASAMBI remote control through App |
|---------------|--|

All Soft triang0 are available in the following colours

