

ring0 Slim Bunch Direct-Indirect

DATA SHEET

PROJECT: _____

TYPE: _____

NOTES: _____

QUANTITY: _____

DATE: _____

GENERAL

Product Code:

RSPB-DI-12108 / RSPB-DI-1086 / RSPB-DI-864

Luminaire Type:

Pendant

Body Construction:

Highest grade extruded aluminum

Body Surface Finishes:

Texture White / Texture Black / Any other RAL color available on request

IP Rating:

40



PHYSICAL

Dimension Φ x H x W:

1200-1000-800x40x20mm

1000-800-600x40x20mm

800-600-450x40x20mm

Fixing System:

1500mm long steel wires with height adjustment system

LED

Light Source:

LED

CCT:

3000K / 4000K / 5700K / TW (Tuneable White)
]2700-6500K

CRI:

80+, 90+ (Available on request)

MacAdam Step:

3

OPTICAL

Light Distribution:

Direct-Indirect

Diffuser:

Satin finished Opal Diffuser

ELECTRICAL

System Wattage:

220W / 180W / 150W

Luminous Flux:

15400lm / 12600lm / 10500lm

Power Factor:

0.94

DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue Dimmable

Bluetooth 4.0 CASAMBI remote control through App