

Groove 40 Pendant Direct-Indirect

DATA SHEET

GENERAL

Product Code:

GPM-40-DI

Luminaire Type:

Pendant

Body Construction:

Highest grade extruded aluminum Aluminum profile single max. length available in 3380mm

Body Surface Finishes:

Natural Silver anodized finish / Texture White / Texture Black / Texture Grey / Any Other RAL color possible on Request (Any Contrast color also possible)

IP Rating:

40

PHYSICAL

Dimension W x H x L\*:

40x100x1130mm

Fixing System:

1500mm long steel wires with height adjustment

LED

Light Source:

LED

CCT:

3000K / 4000K / 5700K / TW (Tunable White)  
2700-6500K

CRI:

80+, 90+, (Available on request)

MacAdam Step:

3

OPTICAL

Light Distribution:

Direct-Indirect

Diffuser:

Satin Finished PC Opal Diffuser

UGR:

UGR < 16

ELECTRICAL

System Wattage:

23W-D / 11W-U / 27W-D / 13W-U

Luminous Flux:

3026 lm at Luminaire level / 3400 lm at Luminaire level

Power Factor:

0.94

DRIVER

Non-Dimmable

DALI Dimmable

0-10V Analogue Dimmable

Bluetooth 4.0 CASAMBI remote control through App

PROJECT:

TYPE:

NOTES:

QUANTITY:

DATE:



\*The length mentioned here is only for a single unit but can be changed as per your preference.

\*customized product, please contact us for required form and patterns.